



# Jetway 1U Type Management Switch Series

**JRL116M-2F-M**  
1U Type Management Switch

**JRL116MP-2F-M**  
1U Type Management Switch with PoE



<b>Chip</b>	Lan chip : IC+	Lan chip : IC+
<b>Dimension</b>	440 * 200 * 44 mm	Power chip : maxim 440 * 200 * 44 mm
<b>Safety</b>	CE, FCC, ROHS	CE, FCC, ROHS
<b>I/O Port</b>	16 * 10/100BaseT(X) 2 * self-switching Gigabit ports LED: Power, port speed, port connection	16 * 10/100BaseT(X) (support POE) 2 * self-switching Gigabit ports LED: Power, PoE, port speed, port connection
<b>Management</b>	Support WEB interface	Support WEB interface ,Support SNMP v1 / v2 / v3
<b>Standards and Agreements</b>	IEEE802.3 10Base-T Ethernet standard IEEE802.3u 100Base-TX Fast Ethernet standard IEEE802.3x full duplex flow control and Backpressure half duplex flow control IEEE802.3ab 1000Base-T Ethernet standard IEEE802.3z Gigabit Ethernet (optical) IEEE802.3x full duplex flow control and Backpressure half duplex flow control IEEE802.3ab link aggregation	IEEE802.3 10Base-T Ethernet standard IEEE802.3u 100Base-TX Fast Ethernet standard IEEE802.3x full duplex flow control and Backpressure half duplex flow control IEEE802.3AB 1000Base-T Ethernet standard IEEE802.3z Gigabit Ethernet (optical) IEEE802.3x full duplex flow control and Backpressure half duplex flow control IEEE802.3ab link aggregation
<b>Network Interface / Wire Specifications</b>	10BASE-T: Category 3 and above non-mask / mask twisted pair (≤100 m) 100BASE-TX: Category 5 and above non-mask / mask twisted pair (≤ 100 m) 1000BASE-T: Category 5 and above non-mask / mask twisted pair (≤100 m)	10BASE-T: Category 3 and above non-mask / mask twisted pair (≤100 m) 100BASE-TX: Category 5 and above non-mask / mask twisted pair (≤ 100 m) 1000BASE-T: Category 5 and above non-mask / mask twisted pair (≤100 m)
<b>PoE Support</b>	N.C	PoE standard: IEEE802.3af, IEEE802.3at, each port provides 15.4W, maximum 30W Pin Definition: V + (RJ45 Pin 1, 2), V- (RJ45 Pin 3, 6) PoE Management: Supports port-based PoE status display and PoE switch control
<b>Power Input / Consumption</b>	AC 90~240V input Built-in 15W open frame power	AC 90~240V input Built-in 270W open frame power
<b>Operating Temp.</b>	0°C ~ +40°C	0°C ~ +40°C
<b>Cooling Method</b>	Mute fan (4020)	Mute fan (4020)
<b>MTBF</b>	100,000 HR	100,000 HR
<b>Warranty</b>	3 years	3 years



## Jetway Information Co., Ltd.

9F, No.207, Sec. 3, Beixin Rd., XindianDist., New Taipei City, 23143, Taiwan

Tel: +886-2-89132711

E-mail: sales@jetway.com.tw

support\_team@jetway.com.tw

Website: www.jetwayipc.com



Z-A95-F